ОХРАНИТЕЛНА ТЕХНИКА > IP Видео Камери

HikVision 8 MP Smart Hybrid Light Fixed Turret Network Camera, 2.8mm, F2.0, IR, White Light up to 30m, 120 dB WDR, H.265+, IP67, built-in microphone, built-in memory card slot, support micro SDXC (512GB), 12Vdc/PoE 6.5W



Модел : DS-2CD1383G2-LIUF
HikVision 8 MP Smart Hybrid Light Fixed Turret Network Camera, 2.8mm, F2.0, IR, White Light up to 30m, 120 dB WDR, H.265+, IP67, built-in microphone, built-in memory card slot, support micro SDXC (512GB), 12Vdc/PoE 6.5W
Тип: IP
Сензор, тип: CMOS
Размер на оптичния сензор: 1/2.7" Progressive Scan CMOS
Резолюция, MP: 8 MP
Фокално разстояние: 2.8 mm, horizontal FOV 113°, vertical FOV 62°, diagonal FOV 134°
Минимална осветеност, lx: Color: 0.01 Lux @ (F2.0, AGC ON), B/W: 0 Lux with IR
IR осветление: IR, White Light up to 30m
Максимална резолюция, pixels: 3840x2160
Формати на компресиране: Main stream: H.265+/H.265/H.264+/H.264; Sub-stream: H.265/H.264 /MJPEG
Скорост на предаване на кадри: Main Stream - 50 Hz: 12.5 fps (3840x2160, 3200x1800, 2688x1520, 1920x1080, 1280x720), 60 Hz: 15 fps (3840x2160, 3200x1800, 2688x1520, 1920x1080, 1280x720); Sub-Stream - 50 Hz:12.5 fps (1280x720, 640x480, 640x360), 60 Hz:15 fps (1280x720, 640x480, 640x360)
Поддържани мрежови протоколи: TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTSP, NTP, IGMP, IPv6, UDP, QoS, FTP, SMTP, UPnP
Мрежов интерфейс: 1 RJ45 10 M/100 M self-adaptive Ethernet port
Безжична мрежа: -
Power Over Ethernet (PoE): IEEE 802.3af, Class 3, max. 6.5 W
Входни/Изходни портове: -
Звук: Built-in Microphone
Захранване: 12 VDC ± 25%, 0.41 A, max. 5 W
Слот за карти: Built-in memory card slot, support microSD/microSDHC/microSDXC card, up to 512 GB
Нощно виждане: IR cut filter

Външен монтаж: yes
Влагозащита: IP67
Вандалоустойчивост: -
Работна температура: -30 °C to 60 °C
Диапазон на влажността при експлоатация: Humidity 95% or less (non-condensing)
Сигурност: Password protection, complicated password, watermark, basic and digest authentication for HTTP, WSSE and digest authentication for Open Network Video Interface, security audit log, host authentication (MAC address)
Размери (Ш, Д, В), mm: 110 x 93 mm

Цена : 223.20 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Вт 30 юни, 2026

November 21, 2026 2:06 a