

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

## ZyXEL CX4800-56F, EU, 48-port 10/25G L3 Aggregation Fiber Switch with 8 100G Uplink (with 2 AC power supply)



Модел : CX4800-56F-EU0101F

ZyXEL CX4800-56F, EU, 48-port 10/25G L3 Aggregation Fiber Switch with 8 100G Uplink (with 2 AC power supply)

Суич, тип: Fixed Port

Общ брой портове: 56

Основни портове, тип: 48 x 10/25GE SFP28

Power Over Ethernet (PoE): -

Uplink портове: 8x100G QSFP28

Свободни (10GB) слотове: -

Управление: via 100/1000BASE-T RJ-45 port for out-of-band IP management; Support NebulaFlex Pro for hybrid mode; Standalone management by Web interface; Cloud management by Nebula Control Center; Management through console, ssh, telnet, SNMP

Stackable: Physical stacking up to 2 units

Fans: Up to 4 field-replaceable, hot-swappable fans

Захранване: Dual hot-swappable AC/DC power supply modules

Routing: Up to 2-unit stacking with Layer 3 static, policy-based, and dynamic routing; IPv4 static route

Памет (Flash, RAM): 64MB/8GB

Капацитет за маршрутизиране/превключване, Gbps: 4 Tbps

Пропускателна способност, Mpps: 2 Bpps

MAC адреси: 32K

VLAN (брой, стандарти): 802.1Q static VLANs/dynamic VLANs: 4K/4K; Port/MAC/Protocol/IP subnet-based VLAN; Private VLAN; VLAN trunking/translation/ingress filtering; 802.1ad VLAN stacking (QinQ)

QoS: No. of hardware queues per port: 8; 802.1p; Storm control: Broadcast, Multicast, Unknown Unicast (DLF); Rate limiting, per IP/TCP/UDP per port; 802.1p Class of Service; Policy based prioritization and etc.

L3 мрежови стандарти: IEEE 802.1D Spanning Tree Protocol (STP); IEEE 802.1w Rapid Spanning Tree Protocol (RSTP); IEEE 802.1s Multiple Spanning Tree Protocol (MSTP); IEEE 802.3ad LACP

IPv6 functionality: ACL packet filtering (IPv4/IPv6); Multiple RADIUS servers (IPv4/IPv6); IPv6 Management; IPv6 Interface; IPv6 MLD Snooping; IPv6 static route; IPv6 default routing; IPv6 ECMP; IPv6 Neighbor Discover

Сигурност: 802.1x; Port security; MAC authentication;



Layer 2 MAC filtering; Layer 3 IP filtering; Layer 4 TCP/UDP socket filtering; Static MAC forwarding; Multiple RADIUS servers (IPv4\*/IPv6); Multiple TACACS+ servers; Login authentication by RADIUS/TACACS+

Размери (Ш, Д, В), mm: 440 x 489 x 45 mm

Опция за монтаж: Rackmount

Цена : 8599.26&nbsp;EUR с ДДС

*Наличност: Този продукт е бил добавен в нашия каталог на Вт 30 юни, 2026*