МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

ZyXEL CX4800-56F, EU, 48-port 10/25G L3 Aggregation Fiber Switch with 8 100G Uplink (with 2 AC power supply)



Модел : CX4800-56F-EU0101F
ZyXEL CX4800-56F, EU, 48-port 10/25G L3 Aggregation Fiber Switch with 8 100G Uplink (with 2 AC power supply)
Суич, тип: Fixed Port
Общ брой портове: 56
Основни портове, тип: 48 x 10/25GE SFP28
Power Over Ethernet (PoE): -
Uplink портове: 8x100G QSFP28
Свободни (10GB) слотове: -
Управление: via 100/1000BASE-T RJ-45 port for out-of-band IP management; Support NebulaFlex Pro for hybrid mode; Standalone management by Web interface; Cloud management by Nebula Control Center; Management through console, ssh, telnet, SNMP
Stackable: Physical stacking up to 2 units
Fans: Up to 4 field-replaceable, hot-swappable fans
Захранване: Dual hot-swappable AC/DC power supply modules
Routing: Up to 2-unit stacking with Layer 3 static, policy-based, and dynamic routing; IPv4 static route
Памет (Flash, RAM): 64MB/8GB
Капацитет за маршрутизиране/превключване, Gbps: 4 Tbps
Пропускателна способност, Mpps: 2 Bpps
MAC адреси: 32K
VLAN (брой, стандарти): 802.1Q static VLANs/dynamic VLANs: 4K/4K; Port/MAC/Protocol/IP subnet-based VLAN; Private VLAN; VLAN trunking/translation/ingress filtering; 802.1ad VLAN stacking (QinQ)
QoS: No. of hardware queues per port: 8; 802.1p; Storm control: Broadcast, Multicast, Unknown Unicast (DLF); Rate limiting, per IP/TCP/UDP per port; 802.1p Class of Service; Policy based prioritization and etc.
L3 мрежови стандарти: IEEE 802.1D Spanning Tree Protocol (STP); IEEE 802.1w Rapid Spanning Tree Protocol (RSTP); IEEE 802.1s Multiple Spanning Tree Protocol (MSTP); IEEE 802.3ad LACP
IPv6 functionality: ACL packet filtering (IPv4/IPv6); Multiple RADIUS servers (IPv4/IPv6); IPv6 Management; IPv6 Interface; IPv6 MLD Snooping; IPv6 static route; IPv6 default routing; IPv6 ECMP; IPv6 Neighbor Discover
Сигурност: 802.1x; Port security; MAC authentication;

November - 2020, 9:5

Layer 2 MAC filtering; Layer 3 IP filtering; Layer 4 TCP/UDP socket filtering; Static MAC forwarding; Multiple RADIUS servers (IPv4*/IPv6); Multiple TACACS+ servers; Login authentication by RADIUS/TACACS+
Размери (Ш, Д, В), mm: 440 x 489 x 45 mm
Опция за монтаж: Rackmount

Цена : 8599.96 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Вт 30 юни, 2026

November 3, 2026, 9:50 pm