

ОХРАНИТЕЛНА ТЕХНИКА > IP Видео Декодери

HikVision 32-ch 1U K Series AcuSense 4K NVR, Up to 12 MP (12x1080p/2x12MP), H.265+, 2 SATA HDD up to 16TB each, 2 USB, Video input: HDMI 4K, VGA 1920 x 1080/60 Hz, 12Vdc, 3.3 A



Модел : DS-7632NXI-K2(D)

HikVision 32-ch 1U K Series AcuSense 4K NVR, Up to 12 MP (12x1080p/2x12MP), H.265+, 2 SATA HDD up to 16TB each, 2 USB, Video input: HDMI 4K, VGA 1920 x 1080/60 Hz, 12Vdc, 3.3 A

Тип: IP Recorder

Брой канали: 32 (IP Video Input)

HDMI: 1-ch, 4K (3840 x 2160)/30 Hz, 2K (2560 x 1440)/60 Hz, 1920 x 1080/60 Hz, 1600 x 1200/60 Hz, 1280 x 1024/60 Hz, 1280 x 720/60 Hz, 1024 x 768/60 Hz

VGA: 1-ch, 1920 x 1080/60 Hz, 1280 x 1024/60 Hz, 1280 x 720/60 Hz

Видео изходен режим: HDMI/VGA independent output

Капацитет: Incoming: 256 Mbps, Outgoing: 160 Mbps

Аудио: 1-ch, RCA (Linear, 1 kOhm); Audio Output: 1-ch, RCA (2.0 Vp-p, 1 kOhm, using the audio input)

Видео компресия: H.265/H.265+/H.264+/H.264

Аудио компресия: G.711ulaw/G.711alaw/G.722/G.726/AAC

Резолюция на запис: 12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF

Дистанционна връзка: 128

Мрежови протоколи: TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP, HTTP, HTTPS

Мрежов интерфейс: 1 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface

Спомагателен интерфейс: 2 SATA interfaces (Capacity: Up to 10 TB capacity for each HDD); Front panel: 1x USB 2.0; Rear panel: 1x USB 2.0; Alarm In/Out: 4/1

Захранване: 12 VDC, 3.3 A; Consumption: <= 15 W (without HDD)

Power Over Ethernet (PoE): -

Размери (Ш, Д, В), mm: 385 x 315 x 52 mm

Тегло, g: <= 1 kg

Цена : 426.00 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на 06 август, 2026