

ОХРАНИТЕЛНА ТЕХНИКА > IP Видео Декодери

HikVision 4-ch 1U K Series AcuSense 4K NVR, Up to 2-ch@12 MP (2x12 MP/4x8 MP/8x4 MP/16x1080p), H.265+, 1 SATA HDD up to 16TB, 2x USB 2.0, Video input: HDMI 1-ch, 4K (3840x2160)/30 Hz, VGA 1-ch, 1920x1080/60 Hz, Audio Output: 1-ch, RCA (Linear, 1 kOhm)



Модел : DS-7604NXI-K1(D)

HikVision 4-ch 1U K Series AcuSense 4K NVR, Up to 2-ch@12 MP (2x12 MP/4x8 MP/8x4 MP/16x1080p), H.265+, 1 SATA HDD up to 16TB, 2x USB 2.0, Video input: HDMI 1-ch, 4K (3840x2160)/30 Hz, VGA 1-ch, 1920x1080/60 Hz, Audio Output: 1-ch, RCA (Linear, 1 kOhm)

Тип: IP Recorder

Брой канали: 4 (IP Video Input)

HDMI: 1-ch, 4K (3840 x 2160)/30 Hz, 2K (2560 x 1440)/60 Hz, 1920 x 1080/60 Hz, 1600 x 1200/60 Hz, 1280 x 1024/60 Hz, 1280 x 720/60 Hz

VGA: 1-ch, 1920 x 1080/60 Hz, 1280 x 1024/60 Hz, 1280 x 720/60 Hz

Видео изходен режим: HDMI1/VGA simultaneous output

Капацитет: Incoming: 40 Mbps, Outgoing: 80 Mbps

Аудио: 1-ch, RCA (2.0 Vp-p, 1 kOhm, using the audio input); Audio Output: 1-ch, RCA (Linear, 1 kOhm)

Видео компресия: H.265/H.265+/H.264+/H.264

Аудио компресия: G.711ulaw/G.711alaw/G.722/G.726/AAC

Резолюция на запис: 12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF

Дистанционна връзка: 128

Мрежови протоколи: TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP, HTTP, HTTPS

Мрежов интерфейс: 1 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interface

Спомагателен интерфейс: 1 SATA interface (Capacity: Up to 16 TB capacity for each HDD); Front panel: 1x USB 2.0; Rear panel: 1x USB 2.0

Захранване: 12 VDC, 1.5 A; Consumption: <= 10 W (without HDD)

Power Over Ethernet (PoE): -

Размери (Ш, Д, В), mm: 320 x 240 x 48 mm

Тегло, g: <= 1 kg

Цена : 188.40 EUR с ДДС



Наличност: Този продукт е бил добавен в нашия каталог на Чт 06 август, 2026

August 22, 2026, 6:12 am