МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

Cisco Catalyst 1200 8-port GE, Desktop, Ext PS, PoE Input



Модел : C1200-8T-D
Cisco Catalyst 1200 8-port GE, Desktop, Ext PS, PoE Input
Суич, тип: Fixed Port
Общ брой портове: 8
Основни портове, тип: 10/100/1000Base-T
Power Over Ethernet (PoE): 1x PoE input (802.3af) on port 1 or AC power
Uplink портове: -
Свободни (10GB) слотове: -
Управление: Network PnP, Web user interface, Cisco Business mobile app, Cisco Business Dashboard, SNMP, MIBs, RMON, DHCP, CLI and etc.
Stackable: -
Fans: Fanless
Захранване: 100 to 240V 50 to 60 Hz, external
Routing: Layer 3 static routing
Памет (Flash, RAM): 512 MB (Flash), 1 GB DDR4 (DRAM), 1.5 MB (Packet buffer)
Капацитет за маршрутизиране/превключване, Gbps: 16 Gbps
Пропускателна способност, Mpps: 11.90 Mpps
MAC адреси: 8000 addresses
VLAN (брой, стандарти): Support for up to 255 active VLANs simultaneously; Port-based and 802.1Q tag-based VLANs, Management VLAN, Guest VLAN, Auto Surveillance VLAN (ASV), Voice VLAN
QoS: 8 hardware queues; Port based, 802.1p VLAN priority based, IPv4/v6 IP precedence/Type of Service (ToS)/DSCP based, Differentiated Services (DiffServ), classification and re-marking ACLs, trusted QoS
L2 мрежови стандарти: IEEE 802.3, IEEE 802.3u/ab/ad/z/x/af/at; IEEE 802.1D (STP)/1Q/p VLAN/w RSTP/s Multiple STP/X Port Access Authentication; RFC
IPv6 functionality: IPv6 host mode, IPv6 over Ethernet, Dual IPv6/IPv4 stack, IPv6 Neighbor Discovery (ND), IPv6 stateless address auto-configuration, Path MTU discovery, DAD, ICMP v6, IPv6 over IPv4 network with ISATAP
Сигурност: SSL, SSH, IEEE 802.1X (authenticator role): RADIUS authentication, guest VLAN, single/multiple host mode, and single/multiple sessions; STP; SCT; SSD, Trustworthy systems, Port security, Storm control, DoS prevention, ACLs
Размери (Ш, Д, В), mm: 160 x 128 x 30 mm

November 2, 2026, 8:48 PM

Опция за монтаж: Desktop

Цена : 183.24 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Ср 02 септември, 2026

November 2, 2026, 8:48 pm