

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

Cisco Catalyst 1300 24-port GE, 4x1G SFP



Модел : C1300-24T-4G

Cisco Catalyst 1300 24-port GE, 4x1G SFP

Суич, тип: Fixed Port

Общ брой портове: 28

Основни портове, тип: 24x 10/100/1000Base-T

Power Over Ethernet (PoE): -

Uplink портове: 4xSFP

Свободни (10GB) слотове: -

Управление: Cisco Business Dashboard; Cisco Business mobile app; Cisco Network Plug and Play (PnP) agent; Web user interface; SNMP; MIB; RMON; RSPAN; sFlow agent; DHCP; SCP; Other: Traceroute, single IP management, HTTP/HTTPS, SSH, RADIUS and etc.

Stackable: -

Fans: Fanless

Захранване: 100-240V 50-60 Hz, internal, universal

Routing: Dynamic Layer 3 routing

Памет (Flash, RAM): 512 MB (Flash), 1 GB DDR4 (DRAM), 1.5 MB (Packet buffer)

Капацитет за маршрутизиране/превключване, Gbps: 56 Gbps

Пропускателна способност, Mpps: 41.66 Mpps

MAC адреси: 16 000 addresses

VLAN (брой, стандарти): Support for up to 4093 VLANs simultaneously; Port-based and 802.1Q tag-based VLANs, MAC-based VLAN, protocol-based VLAN, IP subnet-based VLAN; Management VLAN;

Private/Guest/unauthenticated/Auto

surveillance/CPE/Voice/Dynamic/Multicast TV VLAN

QoS: 8 hardware queues; Strict priority and WRR; Port-based, 802.1p VLAN priority-based, IPv4/v6 IP precedence/Type of Service (ToS)/DSCP-based, Differentiated Services (DiffServ), classification and remarking ACLs, trusted QoS Queue assignment based on DSCP

L2 мрежови стандарти: IEEE 802.3, IEEE 802.3u/ab/ad/z/x/af/at; IEEE 802.1D (STP)/1Q/p VLAN/w RSTP/s Multiple STP/X Port Access Authentication; RFC

IPv6 functionality: IPv6 host mode, IPv6 over Ethernet, dual IPv6/IPv4 stack; IPv6 neighbor and router discovery (ND); DAD, ICMP; DHCPv6; IPv6 over IPv4 network with ISATAP tunnel support; IPv6 QoS; ACL; First Hop Security; MLD

Сигурност: SSH, SSL, IEEE 802.1x (authenticator)

role):RADIUS authentication and accounting, MD5 hash, guest VLAN, unauthenticated VLAN, single/multiple host mode, and single/multiple sessions; MAC/Web-based authentication; STP; DHCP; IPSG; DAI; IPMB; SCT; SSD; ACLs

Размери (Ш, Д, В), mm: 445 x 240 x 44 mm

Опция за монтаж: Rackmount

Цена : 613.80 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Ср 02 септември, 2026