
МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

Cisco Catalyst 1300X 24-port GE, 4x10G SFP+



Модел : C1300X-24T-4X
Cisco Catalyst 1300X 24-port GE, 4x10G SFP+
Суич, тип: Fixed Port
Общ брой портове: 28
Основни портове, тип: 24x 10/100/1000Base-T
Power Over Ethernet (PoE): -
Uplink портове: 4x10G SFP+ (10G Uplink, 25G available for stacking only)
Свободни (10GB) слотове: -
Управление: Cisco Business Dashboard; Cisco Business mobile app; Cisco Network Plug and Play (PnP) agent; Web user interface; SNMP; MIB; RMON; RSPAN; sFlow agent; DHCP; SCP; Other: Traceroute, single IP management, HTTP/HTTPS, SSH, RADIUS and etc.
Stackable: Supports up to 8 switches in a stack. Up to 400 ports managed as a single system with hardware failover
Fans: 1
Захранване: 100-240V 50-60 Hz, internal, universal
Routing: Dynamic Layer 3 routing
Памет (Flash, RAM): 1GB SLC (Flash), 2 GB DDR4 (DRAM), 3MB (Packet buffer)
Капацитет за маршрутизиране/превключване, Gbps: 128 Gbps
Пропускателна способност, Mpps: 95.23 Mpps
MAC адреси: 16 000 addresses
VLAN (брой, стандарти): Support for up to 4093 VLANs simultaneously; Port-based and 802.1Q tag-based VLANs, MAC-based VLAN, protocol-based VLAN, IP subnet-based VLAN; Management VLAN; Private/Guest/unauthenticated/Auto surveillance/CPE/Voice/Dynamic/Multicast TV VLAN
QoS: 8 hardware queues; Strict priority and Weighted Round-Robin (WRR); Class of service: Port-based, 802.1p VLAN priority-based, IPv4/IPv6 IP precedence/Type of Service (ToS)/DSCP-based; Queue assignment based on DSCP and Class of Service (802.1p/CoS); iSCSI
L2 мрежови стандарти: IEEE 802.3, IEEE 802.3u/ab/ad/z/x/af/at; IEEE 802.1D (STP)/1Q/p VLAN/w RSTP/s Multiple STP/X Port Access Authentication; RFC
IPv6 functionality: IPv6 host mode, IPv6 over Ethernet, dual IPv6/IPv4 stack IPv6 neighbor and router discovery (ND), IPv6 stateless address auto-configuration; DAD; IPv6 QoS;l ACL; First Hop Security; Multicast Listener Discovery (MLD

November 4 2020 7:39

v1/2) snooping; MLD
Сигурност: SSH v1 and v2, SCP, SSL, 802.1X: RADIUS authentication and accounting; Web-based authentication; STP; DHCP; IPSG; DAI; IPMB; SCT; SSD; Trustworthy systems; Private VLAN; Layer 2 isolation Private VLAN Edge; Port security; RADIUS/TACACS+; DoS prevention
Размери (Ш, Д, В), mm: 444.3 x 270 x 43.94 mm
Опция за монтаж: Rackmount

Цена : 1020.17 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Ср 02 септември, 2026

November 2, 2026, 7:59 pm