МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

Cisco Catalyst 9200L 24-port 8xmGig, 16x1G, 2x25G, PoE+, Network Essentials



Модел : C9200L-24PXG-2Y-E
Cisco Catalyst 9200L 24-port 8xmGig, 16x1G, 2x25G, PoE+, Network Essentials
Суич, тип: Fixed Port
Общ брой портове: 26
Основни портове, тип: 24 ports full PoE+ (8 mGig ports up to 10G, 16 ports up to 1G)
Power Over Ethernet (PoE): IEEE 802.3at PoE+ (up to 30W per port); Available PoE power with single primary power supply (PWR-C5-600WAC): 370W
Uplink портове: 2x 1/10/25G fixed uplinks
Свободни (10GB) слотове: -
Управление: WebUI is an embedded GUI-based device-management tool that provides the ability to provision the device, to simplify device deployment and manageability, and to enhance the user experience
Stackable: Stacking bandwidth: 160 Gbps
Fans: Fixed redundant
Захранване: PWR-C5-600WAC
Routing: Advanced
Памет (Flash, RAM): Flash: 4 GB; DRAM: 4 GB; Packet buffer: 12MB
Капацитет за маршрутизиране/превключване, Gbps: 292 Gbps; Switch capacity with Stacking: 372 Gbps
Пропускателна способност, Mpps: 229.16 Mpps; Forwarding rate with Stacking: 277 Mpps
MAC адреси: 32 000
VLAN (брой, стандарти): 4; VLAN IDs: 4096; CISCO-PRIVATE-VLAN-MIB, CISCO-VLAN-IFTABLE-RELATIONSHIP- MIB, IEEE 802.1Q VLAN
QoS: Superior QoS includes granular wireless bandwidth management and fair sharing, 802.1p Class of Service (CoS) and Differentiated Services Code Point (DSCP) field classification, SRR scheduling, Committed Information Rate (CIR), eight egress queues per port
L2 мрежови стандарти: IEEE 802.1Q, IEEE 802.1D (STP); RSTP, IEEE 802.1w; MSTP, IEEE 802.1s; PVLAN; IEEE 802.3ad (LACP); LLDP; VTP; BPDU Guard
L3 мрежови стандарти: IP Routing (Static, RIP, OSPF, EIGRP), VLAN Routing (SVI, Routing Between VLANs); Multicast Routing (PIM, IGMP); BGP; IPv6; HSRP; VRRP; GLBP; ACLs; PBR

November 2, 2020, 7:39

IPv6 functionality: IPv6 routing entries: 2000; Ipv6 routing (using OSPFv3 and EIGRPv6); IPv6 addressing
Сигурност: AES-128 MACsec encryption; Secure Segmentation with Software-Defined Access; Cloud Security - Umbrella Integration
Размери (Ш, Д, В), mm: 445 x 350 x 44 mm
Опция за монтаж: Rackmount
Други: Network Essentials licensing

Цена : 8245.27 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Ср 02 септември, 2026

November 2, 2026, 7:39 pm