МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

Cisco Catalyst 9200L 48-port Partial PoE+, 4x10G uplink Switch, Network Essentials

Модел : C9200L-48PL-4X-E
Cisco Catalyst 9200L 48-port Partial PoE+, 4x10G uplink Switch, Network Essentials
Суич, тип: Fixed Port
 Общ брой портове: 52
 Основни портове, тип: 48x10/100/1000Base-T
 Power Over Ethernet (PoE): IEEE 802.3at PoE+ (up to 30W per port), Partial PoE+; Available PoE Power: 370W (Default primary power supply - PWR-C5-600WAC), 740W with Optional secondary power supply - PWR-C5-600WAC
 Uplink портове: 4x10GBase-T
 Свободни (10GB) слотове: No
 Управление: SNMPv1, SNMPv2c, and SNMPv3; RMON I and II standards; Internet Group Management Protocol (IGMP); CLI; TCP; UDP
 Stackable: Cisco StackWise-80 stacking ports: copper-based Cisco StackWise cabling, Stacking hardware (C9200L-STACK-KIT=), Supported stack members: Other C9200L models with same license level (8 Number of members)
 Fans: Fixed redundant
 Захранване: Dual field-replaceable power supplies, Default primary AC power supply: PWR-C5-600WAC
 Routing: Layer 3 Advanced
 Памет (Flash, RAM): Flash memory: 4 GB; RAM: 2 GB DRAM
 Капацитет за маршрутизиране/превключване, Gbps: 176 Gbps
 Пропускателна способност, Mpps: 261.9 Mpps
 MAC адреси: 16000 MAC address
 VLAN (брой, стандарти): VLAN IDs: 1024; IEEE 802.1Q VLAN
 QoS: Granular wireless bandwidth management and fair sharing,802.1p Class of Service (CoS) and Differentiated Services Code Point (DSCP) field classification,Shaped Round Robin (SRR) scheduling,Committed Information Rate (CIR), and eight egress queues per port
 L2 мрежови стандарти: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3bz, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.1D, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.1x-Rev, IEEE 802.3x

November 2020, 7:39

L3 мрежови стандарти: IP unicast routing protocols: Static, Routing Information Protocol Version 1 [RIPv1], and RIPv2, RIPng, Open Shortest Path First [OSPF]

IPv6 functionality: IPv6 routing (using OSPFv3 and EIGRPv6) is supported in hardware for maximum performance; IPv6 addressing is supported on interfaces with appropriate show commands for monitoring and troubleshooting

Сигурност: Enhanced security with AES-128 MACsec encryption, policy-based segmentation, and trustworthy systems

Размери (Ш, Д, В), mm: 445 x 288 x 44

Опция за монтаж: Rackmount

Други: Задължителен е минимум 3-годишен лиценз DNA Essentials.

Цена : 3755.46 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Чт 03 септември, 2026

November 2, 2026, 7:29 pm