МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

Cisco Catalyst 9300 24-port UPOE, Network Advantage



Модел : C9300-24U-A
Cisco Catalyst 9300 24-port UPOE, Network Advantage
Суич, тип: Fixed Port
Общ брой портове: 24
Основни портове, тип: 24x10/100/1000Base-T
Power Over Ethernet (PoE): IEEE 802.3at PoE+ Standard. Available PoE Power: 830W, Cisco UPOE extends the IEEE PoE+ standard to double the power per port to 60 watts.
Uplink портове: 0
Свободни (10GB) слотове: 1 open module slot: Support four optional uplink modules (C9300-NM-4G, C9300-NM-8X, C9300-NM-2Q, C9300-NM-4M). Also supported 3850 network modules (C3850-NM-4-1G, C3850-NM-2-10G, C3850-NM-4-10G).
Управление: SNMPv1, SNMPv2c, and SNMPv3; RMON I and II standards; Internet Group Management Protocol (IGMP); CLI; TCP; UDP
Stackable: Cisco StackWise-480 stacking ports: copper-based Cisco StackWise cabling
Fans: Three field-replaceable fans
Захранване: Dual redundant power supplies, Default power supply: PWR-C1-1100WAC
Routing: Layer 3 Advanced
Памет (Flash, RAM): Flash memory: 16 GB; RAM: 8 GB DRAM
Капацитет за маршрутизиране/превключване, Gbps: 208 Gbps
Пропускателна способност, Mpps: 154.76 Mpps
MAC адреси: 32000 MAC address table size
VLAN (брой, стандарти): VLAN IDs: 4000; IEEE 802.1Q VLAN
QoS: Granular wireless bandwidth management and fair sharing,802.1p Class of Service (CoS) and Differentiated Services Code Point (DSCP) field classification,Shaped Round Robin (SRR) scheduling,Committed Information Rate (CIR), and eight egress queues per port
L2 мрежови стандарти: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3bz, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.1D, IEEE 802.1p, IEEE 802.1Q, IEEE 802.1s, IEEE 802.1w, IEEE 802.1x, IEEE 802.1x-Rev, IEEE 802.3x, IEEE 802.1AE
L3 мрежови стандарти: Advanced IP unicast routing protocols: full OSFP, EIGRP, BGPv4, IS-ISv4

November 2, 2020, 6:48 pm

IPv6 functionality: IPv6 routing; IPv6 addressing; Dual-stack support for IPv4/IPv6 and dynamic hardware forwarding table allocations, for ease of IPv4-to-IPv6 migration; IPv6 support in hardware, providing wire-rate forwarding for IPv6 networks

Сигурност: Encrypted Traffic Analytics (ETA), AES-256 MACsec encryption, Trustworthy systems built with Cisco Trust Anchor Technologies (Image signing, Secure Boot, Cisco Trust Anchor module)

Размери (Ш, Д, В), mm: 445 x 445 x 44

Опция за монтаж: Rackmount

Други: Задължителен е минимум 3-годишен лиценз DNA Advantage.

Цена : 7325.28 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Чт 03 септември, 2026

November 4, 2026, 6:48 pm