МРЕЖОВА ТЕХНИКА > Access Points

Cisco Catalyst 9166I AP (W6E, tri-band 4x4, XOR) w/Reg-E



Модел : CW9166I-E
Cisco Catalyst 9166I AP (W6E, tri-band 4x4, XOR) w/Reg-E
Скорост: 802.11ac: up to 3.4 Gbps (Dual 4x4 80+80 MHz on 5GHz); 802.11n v2: up to 1.5 Gbps (40 MHz with 5GHz and 20 MHz with 2.4GHz); 802.11ax: up to 7.78 Gbps (4x4 160 MHz on 6GHz, 4x4 80 MHz on 5GHz, and 4x4 20 MHz on 2.4GHz)
Антена: Integrated antenna (internal antenna, omnidirectional in azimuth): 2.4 GHz: Peak gain 3 dBi, 5 GHz: Peak gain 5 dBi, 5GHz (XOR): Peak gain 5 dBi, 6 GHz: Peak gain 4 dBi
Интерфейс: 1x 100M/1000M/2.5G/5G Multigigabit Ethernet (RJ-45), Management console port (RJ-45), USB 2.0 at 4.5W
Стандарти: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af/at/bt, IEEE 802.11a/b/g/n/ac/ax, IEEE 802.11h, 802.11d
Сигурност: WPA2-Personal (802.11i), WPA2-Enterprise with 802.1X, WPA3-Personal, WPA3-Enterprise, WPA3-Enhanced Open (OWE), Advanced Encryption Standard (AES), EAP
Захранване: 802.3bt, Cisco Universal PoE (Cisco UPOE), 802.3at Power over Ethernet Plus (PoE+), 802.3af PoE; Max PoE Power Consumption: 30.5W (UPoE); DC power input (54V/MA-PWR-50WAC)
Управление: Allow you to choose between on-premises and cloud management; Cisco Smart Software Manager (SSM)
Размери, mm: (241.3 x 241.3 x 56.9 mm (without mounting brackets)
Тегло, g: 1600 g
Други: Bluetooth 5.1; System memory: 2048 MB DRAM, 1024 MB flash

Цена : 1730.94 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Чт 03 септември, 2026