

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

D-Link 24 PoE 10/100/1000 Base-T port with 4 x 1000Base-T /SFP ports



Модел : DGS-1210-28P

D-Link 24 PoE 10/100/1000 Base-T port with 4 x 1000Base-T /SFP ports

Суич, тип: Fixed Port

Общ брой портове: 28

Основни портове, тип: 24x10/100/1000Base-T

Power Over Ethernet (PoE): Ports 5~24 compliant with IEEE 802.3af Power over Ethernet (PoE) and Ports 1~4 compliant with IEEE 802.3at PoE+ standards; PoE Power Budget: 193 W

Uplink портове: 4xSFP

Свободни (10GB) слотове: No

Управление: Web-based GUI, D-Link Network Assistant Utility, Compact CLI, Telnet Server, TFTP Client, Configurable MDI/MDIX, SNMP v1/v2c/v3, SNMP Trap, Backup/Upgrade firmware, Smart Wizard, Upload/Download Configuration file, RMONv1, Trusted Host, ICMP v6, SNTP

Stackable: No

Fans: Low speed: 47 dBA, High speed: 52.4 dBA

Захранване: Internal Universal Power Supply: 100 - 240 VAC, 50/60 Hz

Routing: Layer 2 Only

Памет (Flash, RAM): -

Капацитет за маршрутизиране/превключване, Gbps: 56 Gbps

Пропускателна способност, Mpps: 41.7 Mpps

MAC адреси: 16000 MAC address table size

VLAN (брой, стандарти): IEEE 802.1Q; VLAN Group: max. 256 static VLAN groups, max. 4094 VIDs; Asymmetric VLAN; Auto Voice VLAN: max. 10 user defined OUI, max. 8 default OUI; Auto Surveillance VLAN

QoS: 802.1p Quality of Service; 8 queues per port; Queue Handling - Strict, Weighted Round Robin (WRR); Bandwidth Control - Port-based (Ingress/Egress, min granularity 10/100/1000 is 64 Kbps); QoS based on: 802.1p Priority Queues, DSCP, ToS, IPv6, TCP/UDP port

L2 мрежови стандарти: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3af, IEEE 802.3at, IEEE 802.3az, IEEE 802.3x, IEEE 802.1D, IEEE 802.1w, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1X

L3 мрежови стандарти: -

IPv6 functionality: IPv6 Ready: Fully IPv6 compatible and ready for enterprise deployment, giving you a head start on

the next Internet standards evolution

Сигурност: Broadcast/Multicast/Unicast Storm Control,
D-Link Safeguard Engine, DHCP Server Screening,
IP-MAC-Port Binding (Smart Binding), 802.1X Port-based
Access Control, ARP Spoofing Prevention, Traffic
Segmentation, SSH v2, SSL, Port Security
Размери (Ш, Д, В), mm: 444 x 210 x 44
Опция за монтаж: Rackmount

Цена : 534.72 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пн 22 юни, 2026