

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

D-Link 28-Port Gigabit Stackable Smart Managed Switch including 4 10G SFP+



Модел : DGS-1510-28X

D-Link 28-Port Gigabit Stackable Smart Managed Switch including 4 10G SFP+

Суич, тип: Fixed Port

Общ брой портове: 28

Основни портове, тип: 24x10/100/1000Base-T

Power Over Ethernet (PoE): No

Uplink портове: 4x10GE SFP

Свободни (10GB) слотове: No

Управление: CLI, Telnet Server, TFTP Client, IPv6 Neighbor Discovery, Configurable MDI/MDIX, SNMP (Supports v1, v2c, v3), SNMP Trap, System Log, DHCP Client, D-Link Network Assistant support, SNTp, ICMPv6, IPv4/v6 Dual Stack, DHCP Auto Configuration, RMON v1

Stackable: Virtual Stacking Support: D-Link Single IP Management, Up to 32 devices per virtual stack, Up to 20G stacking bandwidth; Physical Stacking: Supports Duplex Chain/Ring topology, Up to 40G stacking bandwidth full duplex, Up to 6 units per stack

Fans: 1 x smart fan

Захранване: Internal Universal Power Supply: 100 - 240 VAC, 50/60 Hz

Routing: Layer 3 Lite

Памет (Flash, RAM): -

Капацитет за маршрутизиране/превключване, Gbps: 128 Gbps

Пропускателна способност, Mpps: 95.24 Mpps

MAC адреси: 16000 MAC address table size

VLAN (брой, стандарти): 802.1Q Tagged VLAN, 4K VLAN

Groups, Configurable VID: 0~4094, GVRP, Asymmetric

VLAN, Auto Voice VLAN, Auto Surveillance VLAN, MAC-based VLAN, Protocol-based VLAN

QoS: 802.1p Quality of Service, Queue Handling (Strict Priority Queue(SPQ), Weighted Round Robin(WRR), Deficit Round Robin(DRR), SPQ+WRR), 8 queues per port, Bandwidth Control-Port-based (Ingress/Egress, min. granularity for 10/100/1000 BASE-T ports is 64Kb/s)

L2 мрежови стандарти: IEEE 802.3, IEEE 802.3u, IEEE

802.3ab, 802.3ae, IEEE 802.3x, Spanning Tree Protocol: IEEE

802.1D STP, IEEE 802.1w RSTP, IEEE 802.1s MSTP; IEEE

802.3ad Link Aggregation, IEEE 802.3az Energy Efficient Ethernet

L3 мрежови стандарти: Default Routing, Static Routing: 64 IPv4 Static Route Entries, 32 IPv6 Static Route Entries
IPv6 functionality: IPv6 ready and supports various IPv6 functions such as MLD Snooping, IPv6 security features, and IPv6 Quality of Service (QoS), ensuring seamless integration with next generation networks. IPv4/v6 dual stack functionality

Сигурност: Port Security, Broadcast/Multicast/Unicast Storm Control, Dynamic ARP Inspection, D-Link Safeguard Engine, DHCP Server Screening, ARP Spoofing Prevention, SSH, SSL, Traffic Segmentation, IP-MAC-Port Binding, DoS Attack Prevention, ACLs

Размери (Ш, Д, В), mm: 440 x 210 x 44

Опция за монтаж: Rackmount

Цена : 451.00 EUR с ДДС

Наличност: Този продукт е бил добавен в нашия каталог на Пн 22 юни, 2026