

МРЕЖОВА ТЕХНИКА > СУИЧОВЕ

## D-Link xStack 20-port GE and 4-port Combo 4-port Combo 1000BaseT/SFP plus 4 10GE SFP+



Модел : DGS-3630-28TC/SI

D-Link xStack 20-port GE and 4-port Combo 4-port Combo 1000BaseT/SFP plus 4 10GE SFP+

Суич, тип: Fixed Port

Общ брой портове: 28

Основни портове, тип: 20x10/100/1000Base-T

Power Over Ethernet (PoE): No

Uplink портове: 4 dual personality, 4x10GE SFP

Свободни (10GB) слотове: No

Управление: Web-based GUI, Command Line Interface (CLI), Telnet Server, Telnet Client, SNMP v1/v2c/v3, SNMP Trap, TFTP, FTP, RCP, SMTP, RMONv1 (Supports 1,2,3,9 groups), RMONv2 (Supports ProbeConfig group), D-Link Discover Protocol (DDP), sFlow, Debug Command

Stackable: Physical Stacking: Up to 80 Gbps stacking bandwidth, Up to 9 switches in a stack, Ring/chain topology support; Virtual Stacking/Clustering of up to 32 units: Supports D-Link Single IP Management, Up to 20 Gbps stacking bandwidth

Fans: 2 x smart fans (By default, the fan speed is low. When the temperature inside the chassis is over 36 °C, the fans switch to high speed until the temperature drops below 33 °C)

Захранване: Optional Redundant Power Supply: DPS-500A

Routing: Layer 3 RIP

Памет (Flash, RAM): -

Капацитет за маршрутизиране/превключване, Gbps: 128 Gbps

Пропускателна способност, Mpps: 95.24 Mpps

MAC адреси: 68000 MAC address table size

VLAN (брой, стандарти): VLAN Group: Max. 4K VLAN groups, Max. 4094 VIDs; Multicast VLAN (ISM VLAN for IPv4/IPv6); Voice VLAN; Auto Surveillance VLAN; VLAN Trunking; GVRP: Up to 4K dynamic VLANs; Asymmetric VLAN; 802.1Q; 802.1v Protocol-based VLAN; Double VLAN; Private VLAN

QoS: 802.1p, 8 queues per port, Queue Handling (Strict Priority (SP), Weighted Round Robin (WRR), Strict + WRR, Weighted Deficit Round Robin (WDRR)), Congestion Control, 802.1Qbb Priority-based Flow Control (PFC) for 10 GbE port, Bandwidth Control, Policy Map

L2 мрежови стандарти: IEEE 802.3, IEEE 802.3u, IEEE

802.3ah, IEEE 802.1ag, IEEE 802.3x, IEEE 802.1D, IEEE 802.1w, IEEE 802.1s, IEEE 802.1X, IEEE 802.1Q, IEEE 802.1Qbb, IEEE 802.1p, IEEE 802.1v, IEEE 802.1AX  
L3 мрежови стандарти: Static Route: Max. 512 IPv4 entries, Max. 256 IPv6 entries; IPv4/IPv6 Default Route; BFD (Bidirectional Forwarding Detection) - IPv4/v6 Static Route, RIP, VRRP; RIPv1/v2/ng  
IPv6 functionality: IPv6 Tunnelling: Static, ISATAP, GRE, 6to4; IPv6 Traffic Class; IPv6 Flow Label  
Сигурност: Port Security, Broadcast/Multicast/Unicast Storm Control, D-Link Safeguard Engine, DHCP Server Screening, Dynamic ARP Inspection, IP Source Guard, DHCP Snooping, IPv6 Snooping, Dynamic ARP Inspection (DAI), SSL, SSH, BPDU Attack Prevention  
Размери (Ш, Д, В), mm: 440 x 260 x 44  
Опция за монтаж: Rackmount  
Други: RJ45 and Mini USB console ports for out-of-band CLI management, 10/100/1000BASE-T RJ-45 Ethernet for out-of-band IP management, 1 RJ-45 port Alarm port, 1 USB 2.0 Type A port, Stacking cable and USB flash card not included

Цена : 2064.38&nbsp;EUR с ДДС

*Наличност: Този продукт е бил добавен в нашия каталог на Пн 22 юни, 2026*